



Article Number: 170-03095

Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Black, 200 ft/bulk reel Description:

Base Data		
	Local Order Number	170-03095
	Туре	BSPFR1120B
	Color	Black (BK)
	Features and Benefits	 Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required. Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Braided Sleeving, Expandable, Flame Retardant, 1.5" Dia, PET, Black, 200 ft/bulk reel
Product Dimensions		
	Length L (Imperial)	200.0ft
	Length L (Metric)	61.0m
	Reel Length (imperial)	200.0ft
	Bundle Diameter Min. (Imperial)	1.0"
	Bundle Diameter Min. (Metric)	25.4mm
	Bundle Diameter Max. (Imperial)	2.125"
	Bundle Diameter Max. (Metric)	54.0mm
	Nominal Diameter (Imperial)	1-1/2"
	Nominal Diameter (Metric)	38.1mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	FMVSS 302

generated on: 4/28/2017

170-03095



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	200ft
	Package Quantity (Metric)	60.96m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	3.9lbs
	Weight (Metric)	1.77kg

generated on: 4/28/2017